

## Cleavers

## CS-01A

- Economical Price
- Compact Design



CATEGORY	CS-01A
Fiber Diameter	125 <i>µ</i> m
Coating Diameter	250 ~ 900 µm
Cleave Angle	90°± 0.5°
Cleave Length	Single 5mm to 16mm (coated fiber ≤ 250//m) Single 10mm ~ 16mm, Ribbon 10mm
Blade Life time	50,000
Dimension	57×52×47mm
Weight	247g

<sup>\*</sup> Remark: 5mm cleaving can only be for 250um.

## **CS-01B**

- Single Action(Full Automatic) for cleaving & collecting fiber chips



CATEGORY	CS-01B
Fiber Diameter	125 <i>µ</i> m
Coating Diameter	250 ~ 900 µm
Cleave Angle	90°± 0.5°
Cleave Length	- Single 5mm to 16mm (coated fiber ≤ 250//m) - Single 10mm ~ 16mm, Ribbon 10mm - Exchange Holder : 7mm
Blade Life time	50,000
Dimension	90×51×47mm
Weight	267g

<sup>\*</sup> Remark: 5mm cleaving can only be for 250um.

## CS-03A

- Single Action(Full Automatic) for cleaving & collecting fiber chips



CATEGORY	CS-03A
Fiber Diameter	125 <i>µ</i> m
Coating Diameter	250 ~ 900 µm
Cleave Angle	90°± 0.5°
Cleave Length	- Single 5mm to 16mm (coated fiber ≤ 250//ml) - Single 10mm ~ 16mm, Ribbon 10mm - Exchange Holder : 8mm
Blade Life time	50,000
Dimension	90×51×47mm
Weight	267g

<sup>\*</sup> Remark: 5mm cleaving can only be for 250um.